



There is
a better way ...



WARNING

ONLY INSTALL THIS UNIT ON AUTOMATIC GARAGE DOOR OPERATORS THAT ARE UL 325 APPROVED OR EQUIVALENT

- DOOR MUST HAVE A PRIMARY AND SECONDARY MEANS TO SENSE AND REACT (REVERSE) TO OBSTRUCTIONS WITHIN 2 SECONDS.
- EXAMPLE: YOUR GARAGE DOOR MUST REVERSE WITHIN 2 SECONDS IF REASONABLE PRESSURE IS PLACED ON BOTTOM EDGE OF DOOR WHEN CLOSING (PRESSURE REVERSING SENSOR) AND THE DOOR MUST HAVE A CONTACT SENSOR THAT WILL REVERSE DOOR IF BROKEN (PHOTO EYE BEAM ACROSS DOOR FLOOR.)

DO NOT INSTALL THIS UNIT IF YOU DO NOT HAVE PHOTO EYE BEAM OR SIMILAR SAFETY SYSTEM ON GARAGE DOOR OPERATOR.

THIS UNIT IS TO BE USED AS A SECURITY DEVICE TO ENSURE CLOSURE OF GARAGE DOOR. IT IS NOT INTENDED TO BE USED AS THE PRIMARY MEANS OF CLOSING THE GARAGE DOOR. FOR SAFETY REASONS IT IS RECOMMENDED THAT THE USER KEEP THE DOOR IN SIGHT WHEN CLOSING. MIND EASE SHOULD ONLY BE USED AS A BACK-UP.

THIS UNIT WILL NOT INTERFERE WITH EXISTING GARAGE DOOR OPERATOR SAFETY FEATURES.

DO NOT LEAVE CHILDREN OR PETS UNATTENDED IN OR AROUND THE GARAGE.

This unit can not be used on its own. It is an ADD ON for consumers who already have an Automatic Garage Door Opener.

This unit will only work when garage door is completely open.

IF VEHICLE IS LEFT RUNNING IN GARAGE MAKE SURE DOOR IS FULLY OPEN AND TIMER IS SET FOR APPROPRIATE AMOUNT OF TIME **OR TURN THE UNIT OFF.**

THIS PRODUCT RUNS OFF CLASS 2 POWER CIRCUIT & is **Patent Pending**



*Door and operator must be installed according to manufactures guidelines.

*Test safety features once a month according to manufactures guidelines.

1. Timer Relay Unit
2. 12 “ Wire (white tip)
3. Mounting Hardware/screws/nuts
4. Garage Door Magnetic Micro-Switch
5. 40’ foot Wire (black tip)
6. Metal Angle Mounting Bracket
7. Magnetic Sensor

This product runs off Class 2 Power Circuit.

For more info please visit our Web site at www.garagedoorsecurity.com